

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/056685 A1

(51) International Patent Classification⁷: **B65H 20/16**, 20/18, B23K 26/14

(21) International Application Number:
PCT/AU2003/001703

(22) International Filing Date:
19 December 2003 (19.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002953443 19 December 2002 (19.12.2002) AU

(71) Applicant and

(72) Inventor: MODRA, Christopher, Max [AU/AU]; 277
Springwood Road, Springwood, Queensland 4127 (AU).

(74) Agent: INTELLEPRO; Patent & Trade Mark Attorneys,
(GPO Box 1339, BRISBANE, QLD 4001), Level 7, 102
Adelaide Street, Brisbane, Queensland 4000 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: A LASER CUTTING APPARATUS



(57) Abstract: A laser cutting apparatus (10) is provided for cutting sheet materials. The apparatus (10) includes a table bed (12) having a perforated top surface (40) for a sheet material (32) to be positioned thereon, a gantry (64) extending across the bed and arranged to travel in along the bed, and a carriage (62) arranged to travel along the gantry. The bed has a holding arrangement (46 and 48) for holding the sheet material in position on said bed. The carriage has a laser head (30) with a laser nozzle (36) and is arranged to receive a laser source (32) and to direct a laser beam (42) through the nozzle and towards the bed for cutting the sheet material. An enclosure member (52) having a first low pressure chamber (94) therein is arranged about the laser nozzle. The first chamber has a suction opening beneath the laser nozzle for entraining substantial by-products produced during cutting of the sheet material into the first chamber and for causing a part of the sheet material under the suction opening to be lifted off the top surface. A self cleaning cover (96) with spaced apertures (106) can be rotatably mounted on the enclosure member for removing by-products caught in the selected aperture (106). The carriage may have profiled crease wheels (48,50) for forming crease lines of limited depth into the sheet material. The gantry may have a gripping device (70) arranged to initially lift a small area of a leading edge of the sheet material and then progressively lift other areas of the leading edge onto its lower plate.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.